



FIRST FENCE USA
WE LISTEN. WE CARE. WE DELIVER

Universal Standard Weatherproof Electromagnetic Lock



FEATURES:

SPECIFICATIONS:

Operating Voltage:

Single Voltage: 12 or 24VDC
Dual Voltage: 12/24VDC

Current Draw:

Single Voltage: 500mA/12VDC, 250mA/24VDC
Dual Voltage: 500mA/12VDC, 250mA/24VDC
(at temperature 20°C)

Operating Temperature: -10~55°C (14~131°F)

Humidity: 0~95% non-condensing.

Holding Force: 1200 lbs (545 Kg)

Bond sensor output: 0.5A/20VDC

Dimensions:

Magnet:(L) 220, (W) 62, (D) 40 mm
Armature Plate:(L) 185, (W) 62, (D) 16 mm

Net Weight: 5.1Kg

Surface finish for magnet and armature plate: Zinc plated

Epoxy potting compound rating: E87252 (S) UL94V-0

FUNCTIONS & FEATURES:

- Low maintenance and high reliability
- Stainless steel casing
- MOV provides spike and surge protection
- Anti-Residual magnetism function
- Holding force up to 1200lbs
- Strengthened mounting plate
- Non-handed install
- IPX7 waterproof rating

429 W Kennedale Pkwy, Kennedale, TX 76060



Call our Expert Sales Team for more information

www.firstfenceusa.com | sales@firstfenceusa.com | (945) 941-2111