FIRST FENCE USA

WE LISTEN. WE CARE. WE DELIVER

Temporary Fence Tube Stand Base

Specification Sheet

SPC-TEMP-006A



Call our Expert Sales Team for more information

www.firstfenceusa.com | sales@firstfenceusa.com | (945) 941-2111

FIRST FENCE USA
WE LISTEN. WE CARE. WE DELIVER

Temporary Fence Tube Stand Base

Specification Sheet

SPC-TEMP-006A

Unwavering Stability, Heavy-Duty Support!

The Temporary Fence Tube Stand Base delivers dependable ground-level reinforcement with rapid deployment. Engineered with a high-strength, pre-galvanized carbon steel footprint, this foundational stand offers exceptional balance and rigidity across concrete, packed dirt, and asphalt without shifting under heavy daily site traffic.

The clean, low-profile design minimizes foot-traffic tripping hazards while seamlessly accepting concrete ballast blocks for high-wind stability—ideal for demanding construction sites, industrial yards, and active public events.

Featuring dual vertical insert tubes that accommodate standard 1-3/8" tubular panel frames, this modular base easily adapts to any temporary site boundary for quick setup and compact transport stacking.

Key Features

- High-Strength Pre-Galvanized Steel
  (Withstands harsh weather and site use without rusting)
- Wide Base Stability
  (An expanded footprint that provides exceptional balance)
- Universal Spigot Fit
  (Dual vertical insert tubes for tubular panel frames)
- Ballast Compatible
  (Flat structural profile to accept ballast blocks)
- Clean, Low-Profile Design
  (Minimizes job site tripping hazards)



Suitable For

- Construction & Renovation Sites
- Public Events & Festivals
- Industrial Yards & Warehouses
- Roadwork & Infrastructure Projects
- Emergency Response & Disaster Relief

Product Specifications

HEIGHT	WIDTH	LENGTH	MATERIAL	WEIGHT
9″	18″	36″	Pre-Galvanized Steel	9.7lbs

Often Purchased With



Z-Block Temporary Fence Weight



Z-Weight Temporary Fence Weight

Call our Expert Sales Team for more information

www.firstfenceusa.com | sales@firstfenceusa.com | (945) 941-2111